



Premium Solution with Super-High Speed AC1750 for Elite Performance

CAP1750

3 x 3 AC Dual-Band Ceiling-Mount PoE Access Point



reddot design award
winner 2015

KEY FEATURES


- 802.11AC Dual-Band High Speed:** IEEE 802.11ac concurrent dual-band with 1750Mbps wireless speed.
- Easy Installation:** Ceiling-mount & T-rail mount design with easy installation kit.
- Compact & Durable Housing:** Ultra slim design with UL94-5VB flame-retardant plastic housing.
- Designed for High Density Usage:** Supports up to a hundred users simultaneously, ideal for crowded environments and BYOD (Bring Your Own Device) workplaces.
- Multiple SSIDs for Security Management:** Supports up to 32 SSIDs (16 x 2.4GHz & 16 x 5GHz) ideal for multiple departments, user groups, customers or guests.
- Fast Roaming:** Roams smoothly between APs without lag or interruption, ensuring top performance for video and voice streaming applications.
- Wide Coverage & High Sensitivity:** Adjustable RF output power and high receiver sensitivity for wide coverage across large spaces.
- Seamless Mobility:** 1.5x greater coverage than typical APs for blanket coverage to ensure seamless connectivity for Wi-Fi devices across enterprise environments.
- Power over Ethernet:** Supports IEEE 802.3at PoE as well as included power adapter.
- Built-In RADIUS Server:** With management for up to 256 user accounts.
- Business Environments:** Mainstream choice for SMBs. Suitable for a wide range of commercial applications such as offices, hotels, meeting rooms, schools, campuses, resorts, retail and others.
- Central Management:** Edimax Pro Network Management Suite (NMS), easy and Intuitive web-based central management suite, supports AP array architecture.

The CAP1750 is a powerful wireless solution designed to meet the needs of modern mainstream businesses with the latest IEEE 802.11ac technology for wireless speeds up to 1750Mbps. Industrial-grade performance and build quality combined with user-friendly operation, super-fast wireless speed, an extensive feature set and a practical, ceiling-mount design make an ideal dual-band solution for enterprise environments.

For businesses that demand security, flexibility and speed – the Edimax Pro series has a wide range of potential applications from office environments to schools, campuses, hotels and hospitals. High-density capacity for up to 100 simultaneous users is ideal for BYOD workplaces or other environments with a high volume of users and wireless devices. Multiple SSIDs can be configured for different departments or user groups and a built-in RADIUS server provides additional verification with a scalable AP array architecture for central management of multiple access points. Fast roaming for seamless transitions between access points, Power over Ethernet support (PoE) and an intuitive web-based management interface provides flexibility for deployment and extensive management options for company MIS departments and network administrators.

When performance and security are critical for your business, you need products that are engineered for your industry. The Edimax Pro series is designed to help your business and provide the connectivity that you rely on every day, with safety and effectiveness guaranteed.

Wide Coverage & Multiple SSIDs





BYOD Solution & High Density Networking



Easy Installation Kit

Ceiling mount and T-rail mount with bracket.



Central Network Management Suite



Edimax Pro NMS (Network Management Suite) is a web-based wireless network management system. Company MIS persons can plan and manage Edimax Pro access points' powerful functionality according to their office space using an easy, remote web-based interface which includes a dashboard, map view, traffic statistics and wireless client list for network-wide remote administration. RADIUS settings, WLAN group settings, access control, guest network settings and firmware upgrades can all be managed centrally from a single location to reduce network downtime, aid troubleshooting and optimize network performance. Zone plans and setup wizards are also available for expanding and managing large networks with multiple access points.

3 x 3 AC Dual-Band Ceiling-Mount PoE Access Point

SPECIFICATIONS

Hardware	
LAN Interface	Giga x 1
USB	USB 2.0 x 1 (Optional Ethernet Adapter for 2 nd LAN)
PoE	802.3at
Antenna	Type: 6 x Built-In PIFA (3 x 2.4GHz, 3 x 5GHz) / Gain: 4.38dBi (2.4GHz), 5.34dBi (5GHz) Max.
Power	DC: 12V / 2A 802.3at (PoE Injector Optional)
Dimensions	20.8 (D) x 3.15 (H) cm
Weight	565g
Power Consumption (Full Loading)	15W; 19.2W (With USB)
Mounting	Ceiling
Reset	Y
LED Indicator	1. Power LED 2. Diag LED
Environmental Conditions	Use PoE Switch: Operating Temperature: 0°C (32°F) to 50°C (122°F) Storage Temperature: -20°C (-4°F) to 60°C (140°F) Use Power Adapter: Operating Temperature: 0°C (32°F) to 40°C (104°F) Storage Temperature: -20°C (32°F) to 60°C (140°F) Operating Humidity: 90% or Less Storage Humidity: 90% or Less
Power Saving	802.3az
Internal Buzzer	Y
Housing	UL94-5VB Flammability Rating Plastic
Wireless	
Standard	802.11 a/b/g/n/ac Concurrent Dual-Band
No. of Radios	2
Receiver Sensitivity	≤ -93dBm
Certification	CE/FCC
Fast Roaming	Y
Number of SSIDs	16 (2.4GHz) + 16 (5GHz)
Performance	
Maximum Data Speed	450 + 1300Mbps
Concurrent Clients	Up to 50 Per Radio
Security	
Encryption	WEP / WPA / WPA2
Wireless L2 Isolation	Y
Station Isolation	Y
IEEE 802.1x Authenticator	Y
EAP Authentication	PEAP
Hidden SSID	Y
MAC Address Filter	Y
Wireless STA	Y
Rogue AP Detection (w/ NMS)	Y
Software	
Wireless Mode	AP / WDS AP / WDS Bridge / Repeater
802.1q VLAN	Y (VID = 1-4095)
Spanning Tree	RSTP
QoS	WMM (802.11e) Max Associated Station No.
Pass-Through	IPv6 and VPN (PPTP, L2TP/IPsec)
DSCP (802.1p)	Y
Multicast Rate up to 54Mbps	Y

RF Specifications			
Frequency Band	<ul style="list-style-type: none"> Radio I : 802.11b/g/n 2.412~2.484(GHz) Radio II : 802.11a/n/ac 5.18~5.24(GHz), 5.745~5.825(GHz) (The supported frequency band is restricted by local regulations.)		
Operation Channels	<ul style="list-style-type: none"> 2.4GHz : US/Canada 1-11; 2.412~2.462GHz Europe 1-13; 2.412~2.472GHz Japan 1-14; 2.412~2.484GHz 5GHz : Country dependent for the following ranges: US/Canada: Band 1:36, 40, 44, 48; 5.180~5.240(GHz) Band 4:149, 153, 157, 161, 165; 5.745~5.825(GHz) Europe: Band 1:36, 40, 44, 48; 5.180~5.240(GHz) 		
Transmit Power	<table> <tr> <td> 802.11b 23dBm@1Mbps 23dBm@2Mbps 23dBm@5.5Mbps 23dBm@11Mbps 802.11g 23dBm@6Mbps 23dBm@9Mbps 23dBm@12Mbps 23dBm@18Mbps 23dBm@24Mbps 22dBm@36Mbps 20dBm@48Mbps 19dBm@54Mbps 802.11gn (2.4G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 22dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15 </td><td> 802.11a 22dBm@6Mbps 22dBm@9Mbps 22dBm@12Mbps 22dBm@18Mbps 22dBm@24Mbps 21dBm@36Mbps 19dBm@48Mbps 18dBm@54Mbps 802.11an(5G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 21dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15 802.11ac 23dBm@MCS0 22dBm@MCS1 22dBm@MCS2 21dBm@MCS3 21dBm@MCS4 20dBm@MCS5 19dBm@MCS6 18dBm@MCS7 16dBm@MCS8 15dBm@MCS9 </td></tr> </table>	802.11b 23dBm@1Mbps 23dBm@2Mbps 23dBm@5.5Mbps 23dBm@11Mbps 802.11g 23dBm@6Mbps 23dBm@9Mbps 23dBm@12Mbps 23dBm@18Mbps 23dBm@24Mbps 22dBm@36Mbps 20dBm@48Mbps 19dBm@54Mbps 802.11gn (2.4G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 22dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15	802.11a 22dBm@6Mbps 22dBm@9Mbps 22dBm@12Mbps 22dBm@18Mbps 22dBm@24Mbps 21dBm@36Mbps 19dBm@48Mbps 18dBm@54Mbps 802.11an(5G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 21dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15 802.11ac 23dBm@MCS0 22dBm@MCS1 22dBm@MCS2 21dBm@MCS3 21dBm@MCS4 20dBm@MCS5 19dBm@MCS6 18dBm@MCS7 16dBm@MCS8 15dBm@MCS9
802.11b 23dBm@1Mbps 23dBm@2Mbps 23dBm@5.5Mbps 23dBm@11Mbps 802.11g 23dBm@6Mbps 23dBm@9Mbps 23dBm@12Mbps 23dBm@18Mbps 23dBm@24Mbps 22dBm@36Mbps 20dBm@48Mbps 19dBm@54Mbps 802.11gn (2.4G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 22dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15	802.11a 22dBm@6Mbps 22dBm@9Mbps 22dBm@12Mbps 22dBm@18Mbps 22dBm@24Mbps 21dBm@36Mbps 19dBm@48Mbps 18dBm@54Mbps 802.11an(5G) 23dBm@MCS0/MCS8 22dBm@MCS1/MCS9 22dBm@MCS2/MCS10 21dBm@MCS3/MCS11 21dBm@MCS4/MCS12 20dBm@MCS5/MCS13 19dBm@MCS6/MCS14 18dBm@MCS7/MCS15 802.11ac 23dBm@MCS0 22dBm@MCS1 22dBm@MCS2 21dBm@MCS3 21dBm@MCS4 20dBm@MCS5 19dBm@MCS6 18dBm@MCS7 16dBm@MCS8 15dBm@MCS9		
Receiver Sensitivity	<table> <tr> <td> 802.11b ≤-93dBm@1Mbps ≤-85dBm@11Mbps 802.11g ≤-86dBm@6Mbps ≤-72dBm@54Mbps 802.11gn (2.4G) ≤-83dBm@MCS0 ≤-69dBm@MCS7 ≤-81dBm@MCS8 ≤-66dBm@MCS15 </td><td> 802.11a ≤-90dBm@6Mbps ≤-74dBm@54Mbps 802.11an(5G) ≤-87dBm@MCS0 ≤-69dBm@MCS7 ≤-84dBm@MCS8 ≤-68dBm@MCS15 802.11ac ≤-84dBm@MCS0 ≤-59dBm@MCS9 ≤-80dBm@MCS10 ≤-58dBm@MCS19 </td></tr> </table>	802.11b ≤-93dBm@1Mbps ≤-85dBm@11Mbps 802.11g ≤-86dBm@6Mbps ≤-72dBm@54Mbps 802.11gn (2.4G) ≤-83dBm@MCS0 ≤-69dBm@MCS7 ≤-81dBm@MCS8 ≤-66dBm@MCS15	802.11a ≤-90dBm@6Mbps ≤-74dBm@54Mbps 802.11an(5G) ≤-87dBm@MCS0 ≤-69dBm@MCS7 ≤-84dBm@MCS8 ≤-68dBm@MCS15 802.11ac ≤-84dBm@MCS0 ≤-59dBm@MCS9 ≤-80dBm@MCS10 ≤-58dBm@MCS19
802.11b ≤-93dBm@1Mbps ≤-85dBm@11Mbps 802.11g ≤-86dBm@6Mbps ≤-72dBm@54Mbps 802.11gn (2.4G) ≤-83dBm@MCS0 ≤-69dBm@MCS7 ≤-81dBm@MCS8 ≤-66dBm@MCS15	802.11a ≤-90dBm@6Mbps ≤-74dBm@54Mbps 802.11an(5G) ≤-87dBm@MCS0 ≤-69dBm@MCS7 ≤-84dBm@MCS8 ≤-68dBm@MCS15 802.11ac ≤-84dBm@MCS0 ≤-59dBm@MCS9 ≤-80dBm@MCS10 ≤-58dBm@MCS19		
Management			
Deployment	Standalone: AP mode Master AP mode: Can manage 16 Edimax Pro APs Managed AP mode: Be managed by Edimax Pro AP Controller (APC500) or Edimax Pro Master AP.		
Configuration	HTTP/HTTPS SNMP v1, v2c, v3 CLI (Telnet, SSH)		
RADIUS Server	Built-In		
Auto-Channel	Y		
Private MIB	Y		
Accessory			
Mounting Bracket	Ceiling-Mount Bracket Kit		
Power Adapter	12V / 2A Power Adapter		
Optional Accessories	EU-4306 USB 3.0 Gigabit Ethernet Adapter; GP-101IT IEEE802.3at PoE Injector		



Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.
Copyright © 2015 Edimax Technology Co. Ltd. All rights reserved.

www.edimax.com