









Free EdiView viewer app for iPhone & Android phones













IC-3115W



1.3Mpx Wireless Network Camera

The Edimax IC-3115W is a highly cost-effective network camera designed for easy home monitoring. About the size of an average smartphone, the Edimax IC-3115W can be easily set up on a table or on the wall, so you can always keep an eye on the safety of your pets, property, or loved ones. The Edimax IC-3115W comes in a glossy white finish and a simplistic design, allowing it to blend in perfectly with your home decoration. The Edimax IC-3115W 1.3Mpx Wireless Network Camera is simply the best choice for easy home monitoring.

Edimax Plug-n-View

Edimax Plug-n-View technology makes it easy for you to keep an eye on the safety of your home, family, pets, and assets wherever you go. With Plug-n-View technology, you can set up your Edimax network camera in a few simple steps. The camera also connects to the cloud automatically, so you can access it remotely with a smartphone, tablet, or computer no matter where you are.

Wide Angle, High Quality Videos

The Edimax IC-3115W is built with a wide 1.7mm (28mm equiv.) lens that covers a viewing angle of 74.8 degrees, making it suitable for capturing video footage of a wide area with a single network camera. With a 1.3 megapixel CMOS sensor, this network camera is able to capture SXVGA (1280 x 960) videos at 30 frames per second.

Motion-Triggered Snapshots

The IC-3115W is designed with a powerful multi-area motion detection system. When motion is detected in the specified areas, the network camera will immediately take a snapshot of the detected motion and send the snapshot to the user via email or FTP.

Free Management Software for PC, iPhone, and Android Phones

The Edimax IC-3115W comes with a free 16-channel viewer software for PC that allows users to access and manage up to 16 network cameras simultaneously. This viewer software supports manual, cycle, and scheduled video recording for every surveillance application. Additionally, the IC-3115W network camera's free EdiView viewer app for iPhone and Android phones allows users to access the network camera without a computer at all.



1.3Mpx Wireless Network Camera

IC-3115W

FEATURES & TECHNICAL SPECIFICATIONS

PEATORES & PECHNICAE SI ECHNICATIONS		
Camera	Standards	Interface
*1.3 megapixel CMOS sensor*1.7mm, f/2.4 (approx. 28mm equiv.*View angle: 74.8°	Fast 802.11b/g/nEthernet IEEE802.3/802.3uWireless IEEE	1 Ethernet (RJ-45) port1 Power jack1 Reset/WPS button1 Fixed antenna (2dBi)
Imaging	RF Output Power	Memory
 Video compression: M-JPEG Recording format: AVI(16-channel viewer) Image format: JPEG SXVGA (1280 x 960) at 30fps VGA (640 x 480) at 30fps QVGA (320 x 240) at 30fps 	*11b: 16dBm - 18dBm *11g: 14dBm - 16dBm *11n: 11dBm - 13dBm	*4MB flash *32MB SDRAM
Management	Frequency Band	Operating Conditions
 EdiView Finder (Windows/Mac) 16-channel viewer Web management interface Firmware upgradable iPhone & iPad viewer app Android phone viewer app 	*2.4000-2.4835GHz	*0-40° Celsius *10-90% (non-condensing)
Power	Dimensions & Weight	Certifications
♦5V DC	*65mm x 80mm x 27mm *86g	♦ FCC, CE

SOFTWARE FEATURES

- 3-level user access (administrator/operator/guest)
- Multi-area motion detection
- Sends motion-detected snapshots to email and FTF
- SXVGA (1280 x 960) resolution at 30fps
- WPS support for easy connection
- Viewer software to access 16 network cameras simultaneously
- Free EdiView viewer app for iPhone & Android phones



